



## SYMPPLYDIT LTO-XTF

ULTRA PROFESSIONAL THUNDERBOLT 3 DESKTOP LTO FOR DIT

### ADVANCED-DESIGN THUNDERBOLT 3 ENABLED TAPE STORAGE

**SymplyDIT LTO-XTF** is a unique full-featured archive and transfer system designed specifically for on-set and DIT use with features that can enhance every production and post-production pipeline. SymplyDIT LTO-XTF is based on our advanced desktop SymplyPRO LTO product line that features a rugged metal alloy enclosure and premium whisper-quiet fan and power supply technology, but benefits from unique multi-access technology that combines docking support for Atomos media along with any 2.5" SSD media for fast all-in-one DIT operations.

Unlike others, this is not a re-purposed LTO IT system or highly-design-compromised tape product. The SymplyDIT LTO-XTF was designed by working with media professionals and hearing their needs and wants. We took what they asked for, added high-quality components and SymplyDIT LTO-XTF was born. The flag-ship of the SymplyDIT LTO range, SymplyDIT LTO-XTF features a latest generation full-height LTO-9 tape drive providing staggering read/write speeds up to 400 MB/sec and includes two Thunderbolt 3 ports for device daisy chaining, with one port providing 60 watts for fast device charging. SAS Expansion and SAS host connectivity is also built-in, just in case you need to connected other SAS device(s) to your Thunderbolt computer, or use the device with a non-Thunderbolt workstation.

SymplyDIT LTO configurations feature Linear Tape File System (LTFS) support. Allowing simple drag and drop file operation similar to a conventional hard drive. LTFS can reduce the need for backup or archive software, and allows users to easily interchange data using LTO cartridges or copying data to and from hard disk drives or SSDs.

SymplyATOM (Advanced Tape Operations and Management) is a feature rich software application includes with SymplyDIT LTO that makes operation and maintenance easy. SymplyDIT LTO systems are also certified for use with popular backup and archive utilities for macOS and Windows including YoYotta, Hedge Canister, XenData, and Archiware P5.

If you are looking for a competitive edge to help you meet tight production deadlines or just want to make on-set production and post-production more efficient, you should consider SymplyDIT LTO.

### FEATURES & BENEFITS

- Desktop design with a full-height LTO-9 tape drive and two removable 2.5" SSD bays for fast all-in-one DIT storage
- LTO-9 full-height drive technology offers high endurance and read/write tape speeds up to 400 MB/sec
- Advanced metal alloy enclosure with premium whisper quiet fan and power supply
- SymplyATOM software\* for simplified common management tasks and easy support and maintenance
- Supports LTFS and AES 256-bit encryption
- Media cartridge(s) and cleaning tape included
- Optional ruggedized carry case
- Features Kensington T-Bar™ and support for optional SymplyLOCK™ Thunderbolt 3 cable lock
- 3-Year Warranty (optional 2-Year Extension available)

**GOSYMPPLY.COM**



# SYMPPLYDIT LTO-XTF

## Specifications

<b>Form Factor</b>	Desktop
<b>Dimensions (L x W x H)</b>	30.0 x 21.1 x 13.6 cm (11.8 x 8.3 x 5.4 in)
<b>Weight</b>	6.7 kg (14.7 lbs)
<b>Host Interface</b>	2x Thunderbolt 3 (60W Upstream Charging/15W Downstream Power), 1x miniSAS SFF-8088
<b>Expansion Interface</b>	1x miniSAS SFF-8644
<b>Power Supply</b>	Internal 200W 110V~240V Auto-Switching (Typical 161W)
<b>SSD Reader</b>	2x bays with native support for Atomos Master Caddy II compatible media, or any 2.5" SSD via included adapters

## Performance & Capacity

Drive Type	Media	Speed (Native/Compressed)	Capacity (Native/Compressed)
LTO-9 Full-Height	LTO-9	400 MB/sec (900 MB/sec)	18 TB (45 TB)

## Reliability

Drive Type	MTBF (Hours)	MSBF (Cycles)	Load/Unload (Cycles)
LTO-8 / LTO-7 (per drive)	250,000 @ 100% Duty Cycle	100,000	300,000

## Environmental

	Temperature	Humidity (non-condensing)	Altitude
Operating	15°C to 35°C (59°F to 95°F)	20% to 80%	3,048 m (10,000 ft)
Non-Operating (excludes media)	-40°C to 60°C (-40°F to 140°F)	10% to 90%	12,192 m (40,000 ft)

## Operating System Support

<b>Thunderbolt 3</b>	Apple macOS 10.13+, Microsoft Windows 10, Windows Server 2016, Window Server 2019
<b>SAS</b>	Microsoft Windows, Red Hat Linux, Apple macOS. Check SAS HBA driver support for all OS compatibility.

## Ordering Information

Model	Part Number	Included Accessories
SymplyDIT LTO-XTF LTO-9	SYPRO-DT3L9FH1-A0	(1) LTO-9 Media Tape, (1) LTO Cleaning Tape, 2m Active TB3 Cable, SymplyATOM software (2) 2.5" SSD Adapter Sleds supporting up to 9.5mm drives